



an EnerSys® company

CXPS-E3

400A Power System



- Integrated -48V, 400A power system with front access distribution
- Up to 26 distribution positions in both 5RU, 2.4/3.0kW rectifier option or 7RU, 4kW rectifier option
- Advanced CXC HP controller with touch screen display for full control
- Temperature rated design for harsh outdoor applications from -40 to 65°C
- Wide range AC input for flexible worldwide deployment using a single rectifier
- Industry leading power system density

The CXPS-E3 power system uses high-density rectifiers, a front access distribution center and the advanced CXC HP controller. The CXPS-E3 power system is the ideal solution for small to medium-sized 48VDC applications, providing up to 400 Amps of output current.

With 19" or 23" mounting, high temperature operation and high-power density, it is the perfect solution for a wide variety of installation scenarios including those in harsh, outdoor environments. The distribution center provides up to 26 load breaker positions, integrated shunt and options for LVD. All distribution connections and controller I/O contacts are front accessible. The 2.4/3.0kW and 4kW rectifier options provides the CXPS-E3 power system with the unique capability of having a single module serve a host of AC services (1 Ph, 3 Ph, 208VAC, 240VAC, 277VAC).

The CXC HP controller includes a touch screen GUI for simple and convenient local setup. A built-in web server provides alternate setup via local or remote IP access, using a standard internet browser. System parameters are customizable and provided both locally and remotely.

The CXPS-E3 power system can be easily integrated into customer-provided relay racks or enclosures. It also can be ordered factory installed into various Alpha relay rack configurations and outdoor enclosures. This includes systems with pre-wired battery trays.

CXPS-E3 400A Power System

P/N: Refer online to ordering guide for P/N and configurations

| Electrical | | | |
|-------------------------------|--|--|---|
| Model | | 48V-2.4/3.0kW Rectifier System | 48-4.0kW Rectifier System |
| System Capacity (Max): | | 400A | 400A |
| Input: | Operating Voltage: | 187 to 277VAC (Nominal) | 208 to 277VAC (Nominal) |
| | Extended (High): | 277 to 310VAC | 277 to 320VAC |
| | Extended (Low): | 90 to 187VAC (de-rated O/P power) | 90 to 187VAC (de-rated O/P power) |
| | System AC Requirements: | 19" System: Up to 8 x 20A feeds 23" System: Up to 4 x 40A feeds & 2 x 20A feeds | 19" System: Up to 5 x 30A feeds 23" System: Up to 6 x 30A feeds |
| | Efficiency: | >96% Peak efficiency | >95% Peak efficiency |
| Output: | Current Per Module: | 2.4kW: 50A @ 48VDC (nominal), 25A Max @ 48VDC (120VAC) 3.0kW: 62.5A @ 48VDC (nominal), 32A Max @ 48VDC (120VAC) | 83A @ 48VDC (Nominal I/P) |
| | Rectifier Positions: | 19" System: Up to 8 rectifiers 23" System: Up to 10 rectifiers | 19" System: Up to 5 rectifiers 23" System: Up to 6 rectifiers |
| Mechanical | | | |
| 19" System: | Mounting: | Flush/Center | |
| | Dimensions: | mm: 222H x 482W x 432D (5RU) inches: 8.75H x 19W x 17D (5RU) | mm: 355H x 482W x 432D (7RU) inches: 14H x 19W x 17D (7RU) |
| | Hot Positions: | 21x Load Breakers (or) 16 Load + 5 Battery Breakers 21x sets of 1/4" Studs on 3/8" Centers | |
| | Return Positions: | 21x sets of 1/4" Studs on 3/8" Centers | |
| | Weight (System): | 20.4kg (45lbs) | |
| 23" System: | Mounting: | Flush/Center | |
| | Dimensions: | mm: 222H x 584W x 432D (5RU) inches: 8.75H x 23W x 17D (5RU) | mm: 355H x 584W x 432D (7RU) inches: 14H x 23W x 17D (7RU) |
| | Hot Positions: | 26x Load Breakers (or) 21 Load + 5 Battery Breakers 26x sets of 1/4" Studs on 3/8" Centers | |
| | Return Positions: | 26x sets of 1/4" Studs on 3/8" Centers | |
| | Weight (System): | 25.8kg (57lbs) | |
| Weight (Rectifier): | Module: 1.76kg (3.9lbs) | | Module: 3.9kg (8.6lbs) |
| System Access: | Front access after initial installation | | |
| Controller: | CXC HP | | |
| Environmental | | | |
| Temperature: | -40 to 55°C (-40 to 131°F) 55 to 65°C (-40 to 149°F) de-rated output | | |
| Humidity: | 0 to 95% RH non-condensing | | |
| Elevation: | -500 to 2000m (-1640 to 6600ft) -500 to 4000m (-1640 to 13100ft) with de-rated output | | |
| Agency Compliance | | | |
| Safety: | CSA C22.2 No. 60950-1 | | |



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

07/2020
#0470197-00 REV H