



an EnerSys® company

FXM 1100

Rugged UPS Module



- 1100W/VA UPS designed to operate in extreme environments and provide maximum flexibility while ensuring critical loads remain protected and running during power outages and other power disturbances
- Wide range Automatic Voltage Regulation (AVR) lengthens battery life by providing protection without transferring to backup mode during voltage surges or sags
- Independently programmable control and reporting dry contacts allow monitoring and controlling of key functions
- Temperature compensated battery charging protects batteries from overcharging or undercharging at extreme temperatures, extending the life of the battery
- Local and remote monitoring and control via RS232 port and Ethernet SNMP interface
- UPS panels can be rotated, improving flexibility and viewing convenience

Alpha® FXM is a line of rugged UPS power modules used worldwide where clean backup power is needed.

Designed to perform in the most extreme demanding environments, Alpha® FXM units ensure equipment in security, communications, traffic, industrial environments, and many other critical applications remains safe and protected from power disturbances. Thanks to its powerful programmable battery charger, the FXM is capable of providing the runtime you need. All FXM models are available in 120VAC and 230VAC.

Alpha® FXM family of uninterruptible power supplies (UPS) are designed to provide clean and reliable backup power. Featuring an automatic voltage regulation (AVR), each FXM UPS provides power stability in varied power conditions without using batteries as well as the ability to switch to emergency backup power while maintaining critical loads. The factory installed SNMP card allows remote programming, monitoring and automatic e-mail notification via a web browser.

FXM 1100 Rugged UPS Module

Consult your sales representative for P/N configurations

| Electrical | |
|----------------------------------|---|
| 120VAC Model | |
| Battery String Voltage: | 48VDC |
| Nominal Voltage: | 120VAC |
| Frequency: | 60/50Hz ±5% (auto-detection) |
| Input: | Voltage Range: 85 to 175VAC Current: 15.5A (@ nominal voltage and max battery charging current) |
| Output: | Waveform: Pure sinewave Nominal Voltage: 120VAC Voltage Regulation: ±10% on line mode, ±2% on inverter mode Power at 55°C: 1100W/VA Frequency: Output frequency = Input frequency |
| 230VAC Model | |
| Battery String Voltage: | 48VDC |
| Nominal Voltage: | 230VAC |
| Frequency: | 60/50Hz ±5% (auto-detection) |
| Input: | Current: 8A (@ nominal voltage and max battery charging current) Voltage range: 150 to 328VAC |
| Output: | Waveform: Pure sinewave Nominal Voltage: 230VAC Voltage Regulation: ±10% on line mode, ±2% on inverter mode Power at 55°C: 1100W/VA Frequency: Output frequency = Input frequency |
| Mechanical | |
| Dimensions: | mm: 133H x 394W x 222D inches: 5.22H x 15.5W x 8.75D |
| Weight: | 16kg (35lbs) |
| Communication Interface | |
| Display: | 2 x 20 backlit alpha-numeric LCD |
| Ports: | <ul style="list-style-type: none"> DE-9 Female: Local RS232 Communication RJ45: Remote Communication RJ11: Battery Temperature Compensation |
| Indicators: | <ul style="list-style-type: none"> Green & Red LED's Solid Green: Line Mode Flashing Green: Inverter Mode Flashing Red: Alarm Solid Red: Fault |
| Dry Contacts: | Programmable NO/NC (250VAC, 1A)*, 3 user inputs, ATS |
| Factory Default: | <ul style="list-style-type: none"> C1: On Battery C2, C3: Low Battery C4: Load Shed Timer 1 C5: Alarm C6*: 48VDC @ 500mA C7: User Inputs <ul style="list-style-type: none"> S1: Self test S2: User Input S3: Shutdown(EPO) C8: ATS |
| *C6 is factory configurable only | |

| Environmental | |
|---|--|
| Operating Temp Range*: | -40 to 74°C (-40 to 165°F) |
| Humidity: | Up to 95% (non condensing) |
| Altitude (m/ft): | Up to 3700 (12,000)** |
| Audible noise @ 25°C: | 45dBa @ 1 meter (39in) |
| MTBF (hours): | 150K + as per Telcordia SR-332, 100% duty cycle, full load |
| BTU/Hr: | Normal mode: 22W/75 BTU/hr Backup mode: 242W/825.75 BTU/hr |
| *Derates after 55°C **Derates 2°C per 300m (1000ft) above 1400m (4500ft) | |
| Performance | |
| Typical Output Voltage THD: | <3% (resistive load) |
| Typical Efficiency: | >98% (resistive load) |
| Typical Transfer Time: | <5ms |
| Load Crest Factor: | 3:1 (load dependent) |
| Power Connector Options | |
| 120VAC Model | |
| Input: | Output: |
| Standard |  Terminal Block |
| Optional |  Terminal Block + Dual 5-15R |
|  IEC** |  IEC** |
| 230VAC Model | |
| Standard |  Terminal Block |
| **FXM models with IEC connectors come with 4 lines LCD display instead of the traditional 2 lines display Only available in Kit 0380009-003 | |
| Agency Compliance * * * | |
| Electrical Safety: | UL1778, CSA 22.2 No 107.3; EN62040-1 |
| Marks: |  |
| EMC: | CFR47, Part 15 Subpart B, Class A; CES-003 Class A; EN62040-2 Class A |
| ***Compliance only applies to units with standard input and output connectors. Contact us for compliance information on models with optional power connectors ****CE applies to 230VAC version only | |



Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.